

GTC-Series 恆溫恆濕槽規格

型號	GTC-150					GTC-225					GTC-408					GTC-800																
內部尺寸 (W x H x D)mm	50x60x50					50x75x60					60x85x80					100x100x80																
外部尺寸 (W x H x D)mm	95x150x105					95x165x115					105x175x135					145x190x135																
內容積(liter)	150L					225L					408L					800L																
溫溼度範圍	0°C/-20°C/-40°C/-60°C/-70°C~+100°C (+150°C),10 ~ 98% RH																															
特性	溫溼度控制精度	±0.2°C ; ±2.5%RH																														
	溫溼度分布均度	±0.5°C ; ±4.0%RH																														
	溫溼度解析精度	±0.01°C ; ±0.01%RH																														
	升溫時間 (RT-HT)	°C	100					150					100					150					100					150				
		Min	30					40					30					45					30					45				
降溫時間 (RT-HT)	°C	0	-20	-40	-60	-70	0	-20	-40	-60	-70	0	-20	-40	-60	-70	0	-20	-40	-60	-70	0	-20	-40	-60	-70	0	-20	-40	-60	-70	
	Min	25	40	50	80	90	25	40	50	80	90	25	40	50	80	90	25	40	50	80	90	25	40	50	80	90	25	40	50	80	90	
消耗功率【K.W】	3.0	4.0	6.0	6.0	6.0	3.5	5.5	6.5	8.0	8.5	4.5	6.0	7.5	9.5	9.5	5.5	9.0	10	10.5	10.5												
內部材質	不鏽鋼一級面板																															
外部材質	不鏽鋼一級面板																															
斷熱材質	硬質發泡與玻璃棉																															
系統資訊	循環裝置	多翼式渦輪風扇																														
	冷凍系統	單段/兩段式 空氣冷卻系統																														
	加濕裝置	密閉/半密閉式 壓縮機、電子蒸氣加濕																														
	控制器	可程式控制系統																														
加熱器	鰭片式不鏽鋼軸承加熱器																															
冷卻系統	鰭片&管狀方式散熱																															
加濕給水系統	自動給水系統																															
配件	真空多層自動除霧視窗、電纜孔、室內照明燈、時序信號接點、可調式棚板、調整器																															
保護裝置	過熱保護、斷電開關、壓縮機過載保護、控制系統過載保護、加濕器乾燥與加熱器沸騰保護																															

規格變更恕不另行通知，詳情請洽固緯電子。

溫濕度控制範圍示意圖

